

The Pioneer Gang Plow

Truly in a class of its own the Pioneer 2-bottom gang plow is for the serious horse and mule farmer giving you the ability to greatly increase production. Its conventional steel plow bottoms assure continued parts availability. Ample clearances and full width cover boards provide good trash flow and coverage. Fluted coulters slice through residue for clean furrows. Width and depth of cut are fully adjustable. Furrow and rear wheel steering allow precise control on turns. An elevated operators platform provides a clear and unobstructed view. A convenient D-handle over-center lever, assisted by two adjustable lift springs is all that is needed to easily raise and lower the plow bottoms in and out of the ground. A handy foot latch holds them securely in the raised position.

Features & Specifications

Sizes: 12" or 14" available in right hand (RH) only.

Note: The 12" plow had 14" bottom spacing and the 14" plow has 16" bottom spacing. In most conditions these new tractor type Raydex bottoms perform best when cutting slightly wider than their stated size.

Bottoms: Oliver Raydex type – optional European type Kverneland

Moldboard: replaceable heat treated

Shares: heat treated and readily available

Shin: replaceable heat treated shin piece

Coverboard: replaceable – provides better trash coverage

Coulters: slice through residue for cleaner furrows

Tongue: wood with sliding neckyoke

Frame: heavy tubular steel

Beams: 2-piece reinforced carbon steel

Axles: precision machined carbon steel

Wheel Hubs: 4-bolt with tapered roller bearings

Furrow and Rear Wheel: solid web type – eliminates trash pickup

Land Wheel: heavy duty spoke type

Hitch: ample adjustment for various size hitches

Steering: tongue steers furrow and rear wheel for precise control

Length: 98" overall

Width: 66" overall

Height: 76" minimum